

Hose Type 8/2

Duralife Flex™



Applications

Waterblasting: Heat Exchanger Tube Cleaning
Hydraulics: Instrumentation Packages for Gauges, Pressure Testing for Valves, Tooling and Control Panels

Inner Core: Polyoxymethylene (POM)
Pressure Support: 2 layers of high-tensile steel wire
Outer Cover: Polyamide (PA)
Colour: green, other colours upon request
Temperature: -22F to 140F [-30°C to +60°C]



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,32 inch	0,52 inch	13.050 psi	32.620 psi	5,12 inch	0,134 lbs/ft	0,22 inch	10820101 carbon steel	0,7 inch
8,1 mm	13,3 mm	900 bar	2.250 bar	130 mm	0,200 kg/m	5,5 mm		17,8 mm

Fittings: ID8, Series A and X

Description	Size	Material	Part Number		
male fitting one piece waterblast	1/4"x18 NPTF	carbon steel	30820461X / 30820441/1X		
male fitting one piece waterblast	3/8"x18 NPTF	carbon steel	30820441X / 30820441/1X		
male fitting	1/4"x18 NPTF	carbon steel	30820411A		
male fitting	3/8"x18 NPTF	carbon steel	30820401A		
male fitting DIN3852 T2 form A	G1/4"	carbon steel	30820351A		
male fitting with 60°cone	G1/4"	carbon steel	30820321A		
male fitting flat seal nozzle type	G1/4"	carbon steel	30820381A		
male fitting DIN3852 T2 form A	G3/8"	carbon steel	30820341A		
male fitting with 60°cone	G3/8"	carbon steel	30820301A		
BSP female swivel	G3/8"	carbon steel	20820301A / 50860301		
metric female swivel with O-Ring	M20x1.5	carbon steel	20820201A / 50860201		
metric female swivel with O-Ring	M24x1.5	carbon steel	20820042A / 51361206		
Type M female swivel	3/4"x16 UNF	AISI 316Ti AISI 316Ti carbon steel	20820645A swivel nut / 50840605 swivel nut / 50840601		
JIC female swivel	9/16"x18 UNF	carbon steel	20820601A / 50820601		
JIC female swivel	9/16"x18 UNF	AISI 316 Ti AISI 316 Ti	20820605A swivel nut / 50820605		

----- Additional fittings are available upon request. -----

¹) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

